



DB25 PIN-OUT VIEW FOR DB25

DB25 AND XLR FEMALE WIRING CHART									
XLR	CABLE	PIN 2	PIN 3	PIN 1					
(CHANNEL)	(COLOR)	(RED)	(BLACK)	(BARE)					
1	BROWN	24	12	25					
2	RED	10	23	11					
3	ORANGE	21	9	22					
4	YELLOW	7	20	8					
5	GREEN	18	6	19					
6	BLUE	4	17	5					
7	PURPLE	15	3	16					
8	GRAY	1	14	2					

PART NO.	CABLE LENGTH " X "					
DB25M02XLRF	2.00 FT +/- 1.50 IN					
DB25M03XLRF	3.00 FT +/- 1.50 IN					
DB25M10XLRF	10.00 FT +/- 1.50 IN					

CUSTOMER DRAWING

					-									
						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.								
					UNLESS OTHERWISE SPECIFIED	SIZE	W	WIDTH M			LBS/M	TE	TEMPER	
					1. ALL DIMENSIONS IN INCHES	FINISH		MATERIAL						
					- TWO PLACE DECIMALS ±0.02	SPEC No.				SPEC No.				
С	26637	10/11/10	RS	TJK	- THREE PLACE DECIMALS ±0.005			3:1	 Swiltenerafi			GG®		
В	25891	9/9/08	SRC	TJK		DATE DRAWN	2. 02		APVD					
^	25716	10/03/07	ICK	TJK		9/12/06	JGK	RS	TJK					
A	257 10	10/03/07	JGK	IJK		0.12.00		11/8/10	11/9/10		SHEET 1	OF	1	
REV	ECO NUMBER	DATE	BY	APVD		NAME				PART No				REV
	REVISIONS		DO NOT SCALE DRAWING	DB25M TO 8 FEMALE XLR, RoHS DB25MXLRI				≺F ∣	C					

NOTES:

- 1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- 3. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.
- 4. MATERIALS:

XLR FEMALE CONNECTOR:

HANDLE - ZINC ALLOY, NICKEL PLATED
HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED
INSULATOR - THERMOPLASTIC, GREEN
SOCKET CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED
H.S. TUBING - THERMOPLASTIC
DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS
JACKSCREWS - STAINLESS STEEL

5. THIS PRODUCT IS RoHS COMPLIANT.