



XLR (CHANNEL)	XLR (DESC.)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	XLRM	BROWN	24	12	25
2	XLRM	RED	10	23	11
3	XLRM	ORANGE	21	9	22
4	XLRM	YELLOW	7	20	8
5	XLRM	GREEN	18	6	19
6	XLRM	BLUE	4	17	5
7	XLRM	PURPLE	15	3	16
8	XLRM	GRAY	1	14	2

NOTES:

1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.

**B** 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

**B** 3. MATERIALS:  
 XLR CONNECTORS:  
 HANDLE - ZINC ALLOY, NICKEL PLATED  
 HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED  
 INSULATOR - THERMOPLASTIC, GREEN  
 PINS - SPECIAL COPPER ALLOY, SILVER PLATED  
 H.S. TUBING - THERMOPLASTIC  
 DSUB:  
 CABLE CLAMP - COPPER, NICKEL PLATED  
 SHELL - STEEL, TIN PLATED  
 INSULATORS - THERMOPLASTIC  
 SCREW LOCKS - BRASS, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					SIZE	WIDTH	MULT	LBS/M	TEMPER	
					FINISH			MATERIAL		
					SPEC No.			SPEC No.		
					FIRST USED ON		SCALE 1:2			
					DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft</b> <sup>®</sup>	
					7/16/09	JGK	RS	TJK		
					NAME			PART No.		
					DB25F TO 8-XLRM, RoHS			DB25FXLRM		
					DO NOT SCALE DRAWING					REV <b>B</b>

REV	ECO NUMBER	DATE	BY	APVD
B	26637	10/4/10	RS	TJK
A	26568	7/20/10	RS	TJK